

# “H” TYPE OR FABRICATED 4 – COLUMN TYPE

## TECHNICAL SPECIFICATIONS :

Models	Capacity (Tons)	Ram Size (mm)	Daylight (mm)	Stroke (mm)	Shut Height (mm)	Table Size (LxW) mm	Speeds (mm/sec.)			Electric Motor (H.P.)	No. of Cylinders	Working Ht. (mm)	Bottom Ejector	Slide Locking Arrangement	T-Slots	Working Pr. (Bar)	Weight of m/c (Approx.) Tons
							Approach	Pressing	Return								
HP - 5	5	80	300	300	-	350x300	20-25	5-8	30	3	1 No.(D/A)	700	Optional	-	T - 16	210	2
HP - 10	10	100	350	350	-	350x300	25-30	5-8	30	5	1 No.(D/A)	700	Optional	-	T - 16	210	2.5 to 3
HP - 15	15	120	400	400	-	400x300	25-30	5-8	30-40	5	1 No.(D/A)	700	Optional	-	T - 16	210	3 - 3.5
HP - 20	20	125	400	400	-	400x300	25	5-8	30	5	1 No.(D/A)	700	Optional	-	T - 16	210	3.5
HP - 25	25	125	400	400	-	450x300	25	5-8	30	5	1 No.(D/A)	700	Optional	-	T - 16	210	4 - 5
HP - 30	30	140	400	400	-	450x300	25	5-8	30	5	1 No.(D/A)	700	Optional	-	T - 16	210	4 - 5
HP - 50/60	50/60	200	450	350	100	500x500	70	10	80	7.5	1 + 2	750	Optional	-	T - 16	210	5 to 6
HP - 80	80	220	500	400	100	600x500	70	10	80	7.5	1 + 2	750	Optional	-	T-20	210	6
HP - 100	100	250	600	450	150	600x600	80	10	90	7.5	1 + 2	750	Optional	-	T-20	210	6.5
HP - 125	125	270	700	550	150	700x600	80	10	90	10	1 + 2	750	Optional	-	T-22	210	7
HP - 150	150	300	700	550	150	800x600	80	10	90	15	1 + 2	750	Optional	-	T-22	210	8
HP - 200	200	350	700	500	200	900x800	80	10	90	20	1 + 2	750	Optional	Provided	T-22	210	10
HP - 250	250	400	800	550	250	1000x800	100	10	110	25	1 + 2	750	Optional	Provided	T-22	210	11
HP - 300	300	440	800	600	200	1000x900	100	10	110	30	1 + 2	750	Optional	Provided	T-24	210	12
HP - 350	350	470	900	600	300	1000x1000	120	10	130	30	1 + 2	750	Optional	Provided	T-24	210	14
HP - 400	400	510	900	600	300	1000x1000	120	10	130	40	1 + 2	750	Optional	Provided	T-24	210	15
HP - 500	500	565	1000	700	300	1000x1000	130	10	140	50	1 + 2	750	Optional	Provided	T-24	210	16
HP - 600	600	440	1100	800	300	1200x1000	130	10	140	60	2 + 2	800	Optional	Provided	T-24	210	18
HP - 700	700	470	1200	900	300	1250x1000	150	10	160	60	2 + 2	800	Optional	Provided	T-30	210	22
HP - 800	800	510	1200	800	400	1500x1200	150	10	160	75	2 + 2	800	Optional	Provided	T-30	210	26 to 28
HP - 900	900	500	1500	1100	400	1500x1200	150	10	160	75	2 + 2	800	Optional	Provided	T-30	230	30 to 35
HP - 1000	1000	530	1500	1000	400	1500x1200	180	10	200	75	2 + 2	800	Optional	Provided	T-30	230	35 to 40
HP - 1200	1200	510	1500	1000	500	2000x1500	180	10	200	75	3 + 4	800	Optional	Provided	T-30	230	50
HP - 1500	1500	530	1500	1000	500	2000x1500	200	10	210	100	3 + 4	800	Optional	Provided	T-30	230	55 - 60