

DISPERSION KNEADER

TECHNICAL SPECIFICATIONS:

Moels	Mixing Capacity	Power Required	Tilting Method	Tilting Angle	Exhaust Equipment	Temperature Control	Space Required
SDE-5	5 Ltrs.	7.5.kw	2 H.P. Hydraulics	120° to 140°	0.25 H.P.	Automatic	.75 x 1.25 Mtr.
SDE-15	15 Ltrs.	15.kw	2 H.P. Hydraulics	120° to 140°	0.5 H.P.	Automatic	.75 x 1.25 Mtr.
SDE-25	25 Ltrs.	30.kw	3 H.P. Hydraulics	120° to 140°	1 H.P.	Automatic	1.2 x 2 Mtr.
SDE-35	35 Ltrs.	40.kw	3 H.P. Hydraulics	120° to 140°	1 H.P.	Automatic	1.5x 2.2 Mtr.
SDE-55	55 Ltrs.	55.kw	3 H.P. Hydraulics	120° to 140°	1 H.P.	Automatic	1.8x 2.6 Mtr.
SDE-75	75 Ltrs.	75.kw	5 H.P. Hydraulics	120° to 140°	1 H.P.	Automatic	1.8 x 2.8 Mtr.
SDE-100	105 Ltrs.	90. kw	5 H.P. Hydraulics	120° to 140°	1 H.P.	Automatic	2 x 3 Mtr.
SDE-125	125 Ltrs.	110.kw	5 H.P. Hydraulics	120° to 140°	1 H.P.	Automatic	2.3 x 3.3 Mtr.