

HYDRAULIC SHEARING MACHINES

TECHNICAL SPECIFICATIONS:

		Shearing Capacity Thickness (mm)													
		Mild Steel		Saint less Steel						Stroke Per Min					
Model	Cutting Length (MM)	Nominal Rake	Max. Rake Angle	Nominal Rake	Max. rake Angle	Nominal Rake Angle	Rake Angle Range	Min. Rake Angle	Max. Rake Angle	No. of Hold Down	Holding Force Kgs.	Power H.P.	Packing Dimension L x W x H	Approx. Wgt. Kgs.	
SSM 325	2500	3.15	4	2	3	1degree 15'	0.5-2 degree	28	13	13	2500	5	3200x1850x1950	3500	
SSM 330	3000	3.15	4	2	3	1degree 15'	0.5-2 degree	24	9	15	2500	5	3700x1850x1950	4000	
SSM 412	1250	4	6	3	4	1degree 37'	0.5-3 degree	33	17	5	4000	5	2000x1550x2050	2700	
SSM 415	1500	4	6	3	4	1degree 37'	0.5-3 degree	30	15	8	4500	5	2250x1850x2050	3200	
SSM 420	2000	4	6	3	4	1degree 37'	0.5-3 degree	28	13	11	6200	7.5	2750x1850x2050	3500	
SSM 425	2500	4	6	3	4	1degree 37'	0.5-3 degree	26	8	13	8000	7.5	3300x2250x2400	5000	
SSM 430	3000	4	6	3	4	1degree 37'	0.5-3 degree	24	6	15	10000	10	3700x2250x2400	6000	
SSM 440	4000	4	6	3	4	1degree 45'	0.5-3 degree	22	6	20	12000	10	4500x2250x2400	8100	
SSM 615	1500	6	8	4	6	1degree 45'	0.5-3 degree	24	8	8	6500	10	2250x1900x2100	4000	
SSM 620	2000	6	8	4	6	1degree 45'	0.5-3 degree	22	7	11	6500	10	2750x1900x2100	4300	
SSM 625	2500	6	8	4	6	1degree 45'	0.5-3 degree	28	8	13	8500	15	3300x2250x2500	6000	
SSM 630	3000	6	8	4	6	1degree 45'	0.5-3 degree	24	6	15	10800	15	3800x2250x2500	6500	
SSM 640	4000	6	8	4	6	2degree	0.5-3 degree	24	6	20	13600	20	4800x2250x2500	8200	
SSM 815	1500	8	10	6	8	2degree	0.5-3 degree	22	10	8	10500	15	2250x2050x2200	5200	
SSM 820	2000	8	10	6	8	2 degree	0.5-3 degree	18	8	11	12000	15	2750x2050x2200	6000	
SSM 825	2500	8	10	6	8	2 degree	0.5-3 degree	24	8	13	16500	20	3300x2350x2600	7500	
SSM 830	3000	8	10	6	8	2 degree	0.5-3 degree	20	6	15	18500	20	3800x2350x2600	9000	
SSM 840	4000	8	10	6	8	2 degree	0.5-3 degree	20	8	20	23000	25	4800x2350x2600	12500	
SSM 1015	1500	10	13	8	10	2 degree	0.5-3 degree	20	10	8	10500	15	2250x2050x2300	6000	
SSM 1020	2000	10	13	8	10	2 degree	0.5-3 degree	18	8	11	13000	15	2700x2050x2300	7000	
SSM 1025	2500	10	13	8	10	2 degree	0.5-3 degree	24	8	13	17500	20	3300x2500x2800	9000	
SSM 1030	3000	10	13	8	10	2 degree	0.5-3 degree	20	6	15	20000	20	3800x2500x2800	11500	
SSM 1040	4000	10	13	8	10	2 degree	0.5-3 degree	18	6	20	25000	30	4800x2500x2800	15000	
SSM 1320	2000	13	16	10	13	2 degree	0.5-3 degree	13	5	11	16500	20	2750x2200x2500	7000	
SSM 1325	2500	13	16	10	13	2 degree	0.5-3 degree	15	10	13	32000	25	3350x2600x2800	9000	
SSM 1330	3000	13	16	10	13	2 degree	0.5-3 degree	12	6	15	37000	25	3800x2600x2800	12000	
SSM 1340	4000	13	16	10	13	2 degree	0.5-3 degree	10	4	20	22000	30	4850x2200x2800	15500	
SSM 1620	2000	16	20	13	16	2 degree	0.5-3 degree	13	7	11	22000	25	2750x2200x2600	12000	
SSM 1625	2500	16	20	13	16	2 degree	0.5-3 degree	15	8	13	40000	30	3500x2600x2900	15000	
SSM 1630	3000	16	20	13	16	2 degree	0.5-3 degree	12	6	16	43500	30	4000x2600x2900	17000	
SSM 1640	4000	16	20	13	16	2 degree	0.5-3 degree	10	4	20	30000	30	5100x2750x2900	20000	
SSM 2020	2000	20	25	16	20	2 degree	0.5-3 degree	16	8	11	32000	40	2900x2500x2600	17000	
SSM 2025	2500	20	25	16	20	2 degree	0.5-3 degree	15	8	13	48000	40	3500x2750x3000	18000	
SSM 2030	3000	20	25	16	20	2 degree	0.5-3 degree	12	6	16	52000	40	4000x2750x3000	20000	
SSM 2040	4000	20	25	16	20	2 degree	0.5-3 degree	10	4	20	30000	50	5100x2800x3000	24000	